# Tensor® TECHNICAL DATA SHEET Bullet MULTI-PURPOSE MIST SPRAY

Bullet Bond Multi-purpose Mist Spray is an extremely versatile fine mist spray adhesive that bonds a huge range of lightweight substrates.

Bullet Bond Multi-purpose Mist Spray is easy to apply and dries super fast keeping your projects moving forward.

Multi-purpose mist spray can be applied on only one of the surfaces to be bonded, does not bleed through thin fabrics and dries clear, making it perfect for a huge range of applications.

### **ADVANTAGES**

- Fine Mist Spray
- Instant Tack off
- High Initial Strength
- Quick Dry
- Versatile
- Repositionable

### **SUBSTRATES**

- Fabric
- Fiberglass
- Carbon Fibre
- Foam
- Timber
- Paper & Cardboard
- Some Plastics
- Metal
- Insulation
- Much more

Not suitable for polystyrene

## **DIRECTIONS FOR USE**

This product is designed to be applied to one side of the surfaces to be bonded together, However, It can be used for double sided bonding where required.

Make sure that surfaces are clean, dry and free from dirt, dust, oil, loose paint, wax or grease, etc. For best results, the temperature of the adhesive and the surfaces being bonded should be between 16°C to 27°C. Use with adequate ventilation.

Shake the aerosol well before use. Check compatibility by spraying a small test patch of the adhesive on to the substrate. This product may degrade some substrates.

Spray approx. 20 cm away from the surface, applying a light uniform coat of adhesive.

Place both substrates together and apply even pressure to solidify the bond.

# **ADHESIVE PROPERTIES**

| Total Solids        | 25%  |
|---------------------|--|
| System Flammability | Flammable adhesive with a flammable propellant |
| Dry time            | Immediate                                      |
| Open time           | < 15 Minutes                                   |
| SHELF LIFE          | 18 months from date of manufacture             |

# HANDLING & STORAGE

- Consult Material Safety Data Sheet prior to use.
- Do not store at temperatures over 50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 15°C
- Always test our adhesives to determine suitability for your particular application prior to use.

Copyright © 2021 by Quin Global AU Ltd All rights reserved. This publication or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the publisher.

DISCLAIMER OF WARRANTY: The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.





